

*Choosing environmentally friendly building products today,  
ensures sustainable structures for future generations.*



## Industry first cellulose 3.5" and 5.5" batt insulation

Renewable and Recycled Fibers

Environmentally Responsible

No Scrap Production

Zero Landfill

Class A Building Material

Superior Noise Absorption

STC 50 in 2"x4" Steel Stud Wall

Friction Fit

LEED Eligible

Does not Irritate Skin

Easy to Install

R20 - 5.5" batt

R13 - 3.5" batt



[cmsgreen.com](http://cmsgreen.com)



green

innovative

performance

responsible

value

## Product Performance

- High R-value performance
  - R13 - ECOCELL® 3.5" batt
  - R20 - ECOCELL® 5.5" batt
- Meets or exceeds ASTM testing for both commercial and residential insulation
- Controls and deadens sound due to density of cellulose fibers and non-woven manufacturing process
- Reduces airborne sound transmission from room to room and blocks outdoor noise for a noticeable quietness
- Easy to handle and install, no special equipment required to install
- Manufactured for a tight, friction fit
  - available in 16" or 24"



## Environmental Responsibility

- Made from a combination of recycled and renewable fibers, majority of which is post-consumer recycled newspapers
- Contains a minimum of 70% recycled content
- Zero waste in the manufacturing process
- CMS creates a "greener" manufacturing process by reducing energy use and air pollution during manufacturing
- Environmentally responsible - entirely recyclable

## Product Safety

- Class A fire rating
- Easy to handle compared to fiberglass insulation products
- Contains no harmful airborne particles
- Does not itch or irritate skin
- Contains an EPA registered fungicide to resist the growth of mold



## Physical Properties

• Surface Burning Characteristics ASTM E-84, UL 723	Flame Spread	Class A	15
• Flammability Characteristics ASTM E-970	Smoke Developed	Class A	<450
• Environmental Characteristics ASTM C-739 ASTM C-739	Critical Radiant Flux	Greater than or equal to 0.12w/cm <sup>2</sup>	
• Physical Characteristics ASTM C-518 ASTM C-739 ASTM C-1304	Corrosiveness	Acceptable	
	Fungal Resistance	Acceptable	
• STC 50 in 2"x4" steel stud wall	Thermal Resistance	R-3.6 per inch	
	Moisture Absorption	Acceptable	
	Odor Emission	Acceptable	

cellulose material solutions, llc  
 2472 port sheldon st.  
 jenison, mi 49428  
 +888 968 9877  
 cmsgreen.com

Printed on recycled paper  
 Reorder # 44005 - 11/2012